

# QuikJoint + QuiKHold

**PEEL**

**STICK**

**HEAT**

**Quik Pave Products Inc**

**Roll-Out Over-Banding Joint Tape**  
**Dots & Pads - Asphalt Mastic Fastener/Repair**



# QuikJoint

## Roll Over Joints Like a Pro

### Apply the Best Top Finish on Your Job



**PEEL**



**STICK**



**HEAT**



**DONE**



**QuikJoint Application;** is designed to be an over-banding joint sealing compound, it is an effective means to top-seal / over-band asphaltic concrete longitudinal joints as well as applications where asphaltic pavement abuts rigid cementitious concrete edges. QuikJoint roll out tape, is a **Peel** (remove white release liner); **Stick** (place and press exposed mastic against pavement surface); **Heat** (apply flame heat evenly over entire surface until liquification). This rubberized, non-tracking asphaltic membrane aggressively adheres to a clean, dry, and debris free pavement joint. QuikJoint works to minimize water infiltration into paved surface joints, thus reducing the deterioration of the structural pavement base. It further serves to increase the asphaltic density of a cold flexible pavement joint.

**QuikJoint Benefits:** Rolls are Packaged in a 6 gallon plastic container. Easily and Conveniently extend the life of your flexible pavement by minimizing water penetrating through cracks and joints. Totally eliminate the heating time needed when using a Melter, the labor and mess when using a Pour Pot and the larger equipment necessary to haul specialized pavement joint sealing tools. **QuikJoint**, is a self-adhering rubberized asphaltic tape strip that can be quickly placed over the pavement crack or joint, melted with a minimum amount of torch flame, thus requiring less time and labor costs. After cooling and setting up, QuikJoint asphaltic mastic material is non-tracking.

Width	Best Job Application Chart
1-inch	Infill of Shallow Cracks Prior to Over-banding and/or Sealcoating
2-inch	Over-band Joint/Cracks - Stabilize Flexible Pavement Edges by Minimize Unraveling
4-inch	Best Practice: Joint/Crack Over-band - Utility Cuts - Compliance with Government Specifications
8-inch	Vertical Longitudinal Joints - Increase Pavement Joint Density to Resist Water Infiltration

Product #	QuikJoint Ordering Information	Package
QJ1600	1 inch wide x 50 feet long, 16 rolls (800 lin. ft.)	Pail
QJ2800	2 inch wide x 50 feet long, 8 rolls (400 lin. ft.)	Pail
QJ4400	4 inch wide x 50 feet long, 4 rolls (200 lin. ft.)	Pail
QJ8200	8 inch wide x 50 feet long, 2 rolls (100 lin. ft.)	Pail

### You Save

- Labor
- Mess
- Muscle
- Staging
- Propane
- Money
- Time
- Equipment
- Safety

**QuikJoint Rolls are 50 feet long. Easily Trimmed on Site to Meet Your Job Application**



Heat is required to melt and bond QuikJoint. Do no overheat during . The use of a propane torch presents the possibility of fire. It is your responsibility to take proper precautions when using torches and heating materials. Follow all recommended safety guidelines when handling hot liquified material and open flames. Never allow hot materials or flames to come into contact with the body.

## Contact Your Local Stocking Distributor

or order online at ◀▶ [www.quikpave.com](http://www.quikpave.com)



**QuikHold Dots & Pads :** are a productive and speedy means of securing traffic delineators, road reflectors, speed bumps, cart stalls and other similar traffic control and safety devices. These pre-cut asphalt mastic polymer dots and pads are a fast and effective attachment means; particularly when mechanical fasteners are not desired. Choose the best size for your application.

**QuikHold Large Pads:** are an effective means of stabilizing alligator cracking by minimizing water infiltration, to raise low spots "bird baths" in flexible pavement, to stabilize temporary compacted base stone patches and installed along pavement edges that show signs of unraveling or deterioration. Pads can be easily trimmed to meet size requirements.

**QuikHold Installation:** easily installed by removing the white release paper then placing this newly exposed side on the pavement repair area then heated with a propane torch flame until liquification occurs then Place and Press Traffic Devices. On patch repairs a fine aggregate may be broadcast onto the mastic before it sets up. Asphalt Mastic with polymers is non-tracking material and the repaired area can be used almost immediately.

### QuikHold Application & Ordering Information

Product #	Best Application	Description (custom sizes upon request)	Package
QH-P4100	Reflector Pavement Markers - Bridge Abutments - Signage	100 each - 4 inch square QuikHold Mastic Pads	Box
QH-P1210	Alligatored Areas, Low Spots, Stabilize Base Stone & Edges	10 each - 12 inch square QuikHold Mastic Pads	Box
QH-D6060	Traffic Control Devices, Speed Bumps, Parking Stops	60 each - 6 inch diameter Round Mastic Dots	Box
QH-D8040	Delineators - Reflectors - Control Devices	40 each - 8 inch diameter Round Mastic Dots	Box

**AVAILABLE AT YOUR LOCAL PAVING SUPPLY COMPANY**

or [www.quikpave.com](http://www.quikpave.com) ◀▶ [sales@quikpave.com](mailto:sales@quikpave.com) ◀▶ 888-825-1917



7968 Wesselman Road ◀▶ Cleves, Ohio 45002